



4. WHEN CONSIDERING 7 AND 8 LEAF SPRINGS, USE THE SINGLE AXLE/WIDE SPREAD SPRINGS; 751-06, 752-02/06.
- △ FORWARD AXLE WILL ALWAYS USE 19.25 LONG RADIUS RODS, ONE ADJUSTABLE, ONE NON-ADJUSTABLE. REMAINING AXLE(S) USE 2 ADJUSTABLE RADIUS RODS, LENGTHS AS SHOWN.
- △ MOUNTING HEIGHTS SHOWN USING 354-00 SPG AND .75 SEAT HGT. MOUNTING HEIGHTS OF OTHER SPG/SEAT COMBINATIONS SUBTRACT APPROX .30 FROM THE MOUNTING HEIGHTS FOR THE 49" TANDEM.
- △ REFER TO HUTCHENS INSTALLATION INSTRUCTIONS FOR HANGER & SEAT INSTALLATION.

X/XX BY CHK APPD	
NEXT	LAYOUT DRAWING
SMM 02/17/98	9700 54.5 TA & TRI AX 5'RD
BCC 02/21/98	1/8 2 2 872106
APPD 02/02/98	
HFG 02/02/98	
8942 02/02/98	
REC#711-1	
PROJ#87-2100	