

WARNING

FAILURE TO LOCK THE SLIDING SUSPENSION CAN CAUSE A LOSS OF VEHICLE CONTROL, DEATH, SERIOUS BODILY INJURY, AND PROPERTY DAMAGE.

Hutchens Slider Series (Decal Part Number 16088-01 Rev. D)

THIS TRAILER IS EQUIPPED WITH A SLIDING SUSPENSION THAT MUST BE SECURELY LOCKED PRIOR TO OPERATION. THE SLIDING SUSPENSION IS LOCKED WHEN THE MAIN BODY OF EACH LOCK PIN EXTENDS THROUGH THE HOLES IN THE RAILS. BEFORE PULLING THE TRAILER, THE SLIDING SUSPENSION MUST BE CAREFULLY INSPECTED TO ENSURE IT IS PROPERLY POSITIONED AND THE MAIN BODY OF EACH LOCK PIN DOES EXTEND THROUGH THE HOLE IN THE RAILS. BEFORE PULLING THE TRAILER, APPLY TRAILER BRAKES AND GENTLY ROCK TRAILER BACKWARDS AND FORWARDS TO ENSURE SLIDING SUSPENSION IS SECURE.

TO POSITION THE SLIDING SUSPENSION:

1. Set both tractor and trailer brakes.
2. Remove locator bar from behind slider and move to desired location.
3. To release the lock pins, pull operating handle all the way out and lock in place.
4. Release the tractor brakes and carefully drive forward or backward until the sliding suspension is at the desired location.
5. Release operating handle and visually check all lock pins for locking. The main body of each lock pin must extend through the holes in the rails.
6. Lock locator bar in both body rails immediately behind slider.
7. With the trailer brakes applied, gently rock trailer backward and forward to ensure sliding suspension is properly locked and follow procedures set out above before pulling the trailer. The lock pins must be checked at each stop to ensure each is locked.



Hutchens Industries, Inc., P.O. Box 1427, Springfield, Missouri 65801-1427 Toll Free 1 (800) 654-8824

2. PART DESCRIPTION: SLIDER WARNING LABEL.

MATERIAL: PRESSURE SENSITIVE .003 - .004 FLEXIBLE VINYL.

ADHESIVE: PERMANENT.

SIZE: 7.25 X 3.88.


SHAPE: RECTANGULAR W/SQUARE CORNERS.

FINISH: DIE CUT, SPLIT BACK.

BACKGROUND: PRINTED ONE (1) COLOR SAFETY ORANGE.

LETTERS: SCREENED PRINTED ONE (1) COLOR BLACK.

NOTES: 1. HUTCHENS PART NUMBER: 16088-01; TO APPEAR WITH REVISION LETTER UPON DECAL FACE.

2001191	E	DWG NO. NOW REFLECTS PART NO. WAS 2 SHEETS NOW			06/21/01	GLS	SNM	RSB
2001191	E	2 SEPARATE DWG'S.			06/21/01	GLS	SNM	RSB
2000047	D	PICTURE REVISION TO REFLECT TYPE-SET CHANGE.			02/10/00	ERU	SNM	RSB
ER NO.	SYM	REVISIONS			DATE	BY	CHK	APPD
DRAWN: DCG		DATE: 9/8/89			HUTCHENS INDUSTRIES, INC. SPRINGFIELD, MISSOURI			
CHECK: DCC		DATE: 9/29/89						
APPD COT		DATE: 9/29/89						
MFG APPL: CB		DATE: 10/10/89						
ER: 8927		DATE: 9/29/89						
PROJ/REF NO. REC# 908-04 PROJ# 89-0316		NEXT ASSY:	TITLE : DECAL WARNING SLIDER OPERATION					
			SHEET 1	OF 1	SIZE A	DRAWING NO.: 16088-01		REV. E